



35 Watt High Pressure Sodium

23001 DATA SHEET



**HIGH
PRESSURE
SODIUM**



Dia. = 2.1" (54mm)
MOL = 5.4" (138mm)
LCL = 3.4" (87mm)
Base = Medium (E26)

LU35/D/MED

GENERAL Characteristics

| | |
|--------------------|------------------|
| Lamp Type | HPS Single Ended |
| ANSI Code | S76 |
| Bulb Shape | E17 |
| Base Type | Medium (E26) |
| Bulb Finish | Coated |
| Rated Life | 16000 hours |
| Operating Position | Universal |

PHOTOMETRIC

| | |
|------------------------------------|------------------------|
| Initial Lumens | 2100 |
| Lumens Per Watt | 60 |
| Lamp Lumen Depreciation (LLD) | .90 (90%) @ 8000 hours |
| Correlated Color Temperature | 2100K |
| Chromaticity Coordinates (CIE-x,y) | .522 .423 |
| Color Rendering Index (CRI) | 22 |

PHYSICAL

| | |
|----------------------------|----------------|
| Bulb Diameter | 2.1" (54mm) |
| Max. Overall Length (MOL) | 5.4" (138mm) |
| Light Center Length (LCL) | 3.4" (87mm) |
| Effective Arc Length | N/A |
| Max. Base Temperature (°C) | 190 |
| Max. Bulb Temperature (°C) | 400 |
| Socket Pulse Rating (KV) | 4 |
| Luminaire Type | Enclosed Rated |

ELECTRICAL

| | |
|---------------------------|----|
| Lamp Watts | 35 |
| Lamp Oper. Voltage (Nom.) | 55 |

SUSTAINABILITY

| | |
|-------------------|------------------------|
| Recycling Program | Smartpac® 800-451-2606 |
|-------------------|------------------------|

NOTES

(800) 451-2606
or (440) 248-3510

Fax: (800) 451-2605
7905 Cochran Road
Glenwillow, Ohio 44139 USA
E-mail: venture@adlt.com
VentureLighting.com

This Product is Recyclable Through  Smartpac
FOR RECYCLING PURPOSE