

250 Watt Pulse Start Lamp

59324

DATA SHEET



Natural White®

MP 250W/H75/T15/PS/EM/950

GENERAL Characteristics

| | |
|--------------------|-----------------------------|
| Lamp Type | MH Pulse Start Single Ended |
| ANSI Code | M138,M153/O |
| Bulb Shape | T15 |
| Base Type | Mogul (EX39) |
| Bulb Finish | Clear |
| Rated Life | 15000 hours |
| Operating Position | Horizontal $\pm 75^\circ$ |

ELECTRICAL

| | |
|---------------------------|-----|
| Lamp Watts | 230 |
| Lamp Oper. Voltage (Nom.) | 133 |

PHOTOMETRIC

| | |
|------------------------------------|-------------------------|
| Initial Lumens | 17000 |
| Lumens Per Watt | 74 |
| Lamp Lumen Depreciation (LLD) | 0.90 (90%) @ 6000 hours |
| Correlated Color Temperature | 5000K |
| Chromaticity Coordinates (CIE-x,y) | .346 .359 |
| Color Rendering Index (CRI) R_a | 90+ |

PHYSICAL

| | |
|--|-----------------------|
| Bulb Diameter | 2.0" (52mm) |
| Max. Overall Length (MOL) | 8.3" (211mm) |
| Light Center Length (LCL) | 5.0" (127mm) |
| Effective Arc Length | 25.2mm |
| Max. Base Temperature ($^\circ\text{C}$) | 210 |
| Max. Bulb Temperature ($^\circ\text{C}$) | 500 |
| Socket Pulse Rating (KV) | 4 |
| Luminaire Type | Open / Enclosed Rated |

SUSTAINABILITY


| | |
|-------------------------------------|------|
| Mercury Amount (mg) | 11.0 |
| Picograms of Hg per Mean Lumen Hour | 48 |

NOTES




- Lamp performance ratings published in this data sheet are based upon operation with magnetic ballasts.
- Operation of position-rated lamps outside of their tolerances will result in poor performance.
- Minimum Starting Temperature: $-40^\circ\text{C}/^\circ\text{F}$.
- To calculate nighttime Scotopic lumens, multiply the lumen rating by the S/P ratio (2.1).



T15



Dia. = 2.0" (52mm)
MOL = 8.3" (211mm)
LCL = 5.0" (127mm)
Base = Mogul (EX39)



(800) 451-2606

6675 Parkland Blvd., Suite 100
Solon, Ohio 44139 USA

E-mail: Venture_Lighting@VentureLighting.com

VentureLighting.com

THIS LAMP CONFORMS TO FEDERAL STANDARD 21 CFR 1040.30
Complies with (CE), Low Voltage (CE), WEEE and RoHS Directives

Warning: This lamp can cause skin burn and eye inflammation from shortwave ultraviolet radiation if outer envelope of the lamp is broken or punctured. Do not use where people will remain for more than a few minutes unless adequate shielding or other safety precautions are used. Lamps that will automatically extinguish when outer envelope is broken or punctured are commercially available.