

ED28



Dia. = 3.5" (90mm) MOL = 8.3" (211mm) LCL = 5.0" (127mm) Base = Mogul (EX39)

MP 175W/U/PS/740 GENERAL Characteristics

Lamp Type	MH Pulse Start Single Ended
ANSI Code	M137, M152/0
Bulb Shape	ED28
Base Type	Mogul (EX39)
Bulb Finish	Clear
Rated Life (V)	15000 hours
Rated Life (H)	11250 hours
Operating Position	Universal

PHOTOMETRIC

Initial Lumens / LPW (V)	16600 / 95	
Initial Lumens / LPW (H)	15000 / 86	
Lamp Lumen Depreciation (LLD)	0.80 (80%) @ 6000 hours	
Correlated Color Temperature	4000K	
Chromaticity Coordinates (CIE-x,y)	.385 .390	
Color Rendering Index (CRI) R _a	68	

PHYSICAL

Bulb Diameter	3.5" (90mm)
Max. Overall Length (MOL)	8.3" (211mm)
Light Center Length (LCL)	5.0" (127mm)
Effective Arc Length	21.6mm
Max. Base Temperature (°C)	210
Max. Bulb Temperature (°C)	400
Socket Pulse Rating (KV)	4
Luminaire Type	Open / Enclosed Rated

ELECTRICAL


Lamp Watts	175
Lamp Oper. Voltage (Nom.)	132


SUSTAINABILITY


Mercury Amount (mg)	21.0
Picograms of Hg per Mean Lumen Hour (V)	105

NOTES

- Nominal color temperature rating is based on Vertical (±15°) operation of the lamp. Off-vertical positions will result in higher color temperature.
- Minimum Starting Temperature: -40°C/°F.







(800) 451-2606

6675 Parkland Blvd., Suite 100 Solon, Ohio 44139 USA

E-mail: Venture_Lighting@VentureLighting.com

VentureLighting.com

THIS LAMP CONFORMS TO FEDERAL STANDARD 21 CFR 1040.30 Complies with (CE), Low Voltage (CE), WEEE and RoHS Directives

Warning: This lamp can cause skin burn and eye inflammation from shortwave ultraviolet radiation if outer envelope of the lamp is broken or punctured. Do not use where people will remain for more than a few minutes unless adequate shielding or other safety precautions are used. Lamps that will automatically extinguish when outer envelope is broken or punctured are commercially available.