# Pulse Start Lamp





Extended Life Lamps



ED37

Dia. = 4.6" (120mm) MOL = 11.5" (292mm) LCL = 7.0" (178mm) Base = Mogul (E39)

## MHL 320W/C/H75/ED37/PS/737 GENERAL Characteristics ELECTRICAL

Lamp Type	MH Pulse Start Single Ended
ANSI Code	M132, M154/E
Bulb Shape	ED37
Base Type	Mogul (E39)
Bulb Finish	Coated
Rated Life	40000 hours
Operating Position	Horizontal ±75°

## **PHOTOMETRIC**

Initial Lumens	28000	
Lumens Per Watt	88	
Lamp Lumen Depreciation (LLD)	0.86 (86%) @ 16000 hours	
Correlated Color Temperature	3700K	
Chromaticity Coordinates (CIE-x,y)	.395 .390	
Color Rendering Index (CRI) Ra	70	

## PHYSICAL

Bulb Diameter	4.6" (120mm)
Max. Overall Length (MOL)	11.5" (292mm)
Light Center Length (LCL)	7.0" (178mm)
Effective Arc Length	N/A
Max. Base Temperature (°C)	210
Max. Bulb Temperature (°C)	400
Socket Pulse Rating (KV)	4
Luminaire Type	Enclosed Rated

#### 320 Lamp Watts 135 Lamp Oper. Voltage (Nom.)


DATA SHE

## **SUSTAINABILITY**


Mercury Amount (mg)	56.0
Picograms of Hg per Mean Lumen Hour	58

## **NOTES**

- Lamp performance ratings published in this data sheet are based upon operation with approved electronic ballasts.
- Operation of position-rated lamps outside of their tolerances will result in poor performance.
- Minimum Starting Temperature: -40°C/°F.
- To calculate nighttime Scotopic lumens, multiply the lumen rating by the S/P ratio (1.7).



### Lumen Maintenance 10 7 Lumens % 25 25 75 50 100 % Life



(800) 451-2606 6675 Parkland Blvd., Suite 100 Solon, Ohio 44139 USA E-mail: Venture\_Lighting@VentureLighting.com

VentureLighting.com

THIS LAMP CONFORMS TO FEDERAL STANDARD 21 CFR 1040.30 Complies with (CE), Low Voltage (CE), WEEE and RoHS Directives

Warning: This lamp can cause skin burn and eye inflammation from shortwave ultraviolet radiation if outer envelope of the lamp is broken or punctured. Do not use where people will remain for more than a few minutes unless adequate shielding or other safety precautions are used. Lamps that will automatically extinguish when outer envelope is broken or punctured are commercially available.

VLI-0992SS11-0822