



MS 400W/HOR/T15/3K GENERAL Characteristics ELECTRICAL

Lamp Type	Standard MH Single Ended
ANSI Code	M59/E
Bulb Shape	T15
Base Type	Mogul POMB (EP39)
Bulb Finish	Clear
Rated Life	15000 hours
Operating Position	Horizontal ±45°

Lamp Watts	400
Lamp Oper. Voltage (Nom.)	135
Dimming	

SUSTAINABILITY

Mercury Amount (mg)	54.0
Picograms of Hg per Mean Lumen Hour	146

PHOTOMETRIC

Initial Lumens	38000
Lumens Per Watt	95
Lamp Lumen Depreciation (LLD)	0.65 (65%) @ 6000
Correlated Color Temperature	3200K
Chromaticity Coordinates (CIE-x,y)	.420 .395
Color Rendering Index (CRI) R _a	65

NOTES

- Lamp performance ratings published in this data sheet are based upon operation with magnetic ballasts.
- Operation of position-rated lamps outside of their tolerances will result in poor performance.
- Permitted rotation about axis ± 15°.
- To calculate nighttime Scotopic lumens, multiply the lumen rating by the S/P ratio (1.4).


HOR ±45° Horizontal





Dia. = 2.0" (52mm) MOL = 9.8" (248mm) LCL = 5.8" (146mm) Base = Mogul POMB (EP39)

PHYSICAL

Bulb Diameter	2.0" (52mm)
Max. Overall Length (MOL)	9.8" (248mm)
Light Center Length (LCL)	5.8" (146mm)
Effective Arc Length	30.9 mm
Max. Base Temperature (°C)	210
Max. Bulb Temperature (°C)	500
Socket Pulse Rating (KV)	-
Luminaire Type	Enclosed Rated







(800) 451-2606

6675 Parkland Blvd., Suite 100 Solon, Ohio 44139 USA

E-mail: Venture_Lighting@VentureLighting.com

VentureLighting.com

THIS LAMP CONFORMS TO FEDERAL STANDARD 21 CFR 1040.30 Complies with (CE), Low Voltage (CE), WEEE and RoHS Directives

Warning: This lamp can cause skin burn and eye inflammation from shortwave ultraviolet radiation if outer envelope of the lamp is broken or punctured. Do not use where people will remain for more than a few minutes unless adequate shielding or other safety precautions are used. Lamps that will automatically extinguish when outer envelope is broken or punctured are commercially available.