



### MH 1500W/HBU

#### GENERAL Characteristics

Lamp Type	Standard MH Single Ended
ANSI Code	M48/E
Bulb Shape	BT56
Base Type	Mogul (E39)
Bulb Finish	Clear
Rated Life	3000 hours
Operating Position	Base Up $\pm 105^\circ$

#### ELECTRICAL

Lamp Watts	1500
Lamp Oper. Voltage (Nom.)	268
Dimming	

#### SUSTAINABILITY


Mercury Amount (mg)	147.0
Picograms of Hg per Mean Lumen Hour	358

#### PHOTOMETRIC

Initial Lumens	161000
Lumens Per Watt	107
Lamp Lumen Depreciation (LLD)	0.85 (85%) @ 1200
Correlated Color Temperature	3400K
Chromaticity Coordinates (CIE-x,y)	.410 .385
Color Rendering Index (CRI) $R_a$	65

#### NOTES

- Lamp performance ratings published in this data sheet are based upon operation with magnetic ballasts.
- Operation of position-rated lamps outside of their tolerances will result in poor performance.
- Dimming applicable only when lamp is installed in the Base Up  $\pm 15^\circ$  (BU  $\pm 15^\circ$ ) position.
- To calculate nighttime Scotopic lumens, multiply the lumen rating by the S/P ratio (1.4).




BU  $\pm 105^\circ$   
Base Up




#### PHYSICAL

Bulb Diameter	7.0" (180mm)
Max. Overall Length (MOL)	15.3" (391mm)
Light Center Length (LCL)	9.5" (241mm)
Effective Arc Length	90.6 mm
Max. Base Temperature ( $^\circ\text{C}$ )	250
Max. Bulb Temperature ( $^\circ\text{C}$ )	430
Socket Pulse Rating (KV)	-
Luminaire Type	Enclosed Rated

BT56



Dia. = 7.0" (180mm)  
MOL = 15.3" (391mm)  
LCL = 9.5" (241mm)  
Base = Mogul (E39)



(800) 451-2606

6675 Parkland Blvd., Suite 100

Solon, Ohio 44139 USA

E-mail: [Venture\\_Lighting@VentureLighting.com](mailto:Venture_Lighting@VentureLighting.com)

[VentureLighting.com](http://VentureLighting.com)

THIS LAMP CONFORMS TO FEDERAL STANDARD 21 CFR 1040.30  
Complies with (CE), Low Voltage (CE), WEEE and RoHS Directives

**Warning:** This lamp can cause skin burn and eye inflammation from shortwave ultraviolet radiation if outer envelope of the lamp is broken or punctured. Do not use where people will remain for more than a few minutes unless adequate shielding or other safety precautions are used. Lamps that will automatically extinguish when outer envelope is broken or punctured are commercially available.